



НТК - КАМЕРНЫЕ ПЕЧИ С МЕТАЛЛИЧЕСКОЙ ТЕПЛОИЗОЛЯЦИЕЙ

The metallic HTK range of Carbolite high temperature furnaces consists of metal heaters made of Molybdenum or Tungsten.

The HTK series, made of metal, is available in four distinct sizes. The smaller HTKs with capacities of 8 and 25 liters are usually used in laboratories for research and development. The larger 80 and 120-litre furnaces are mostly utilized as pilot manufacturing systems or for large-scale production. The front door design of these furnaces allows for easy loading and unloading.

The metallic furnaces are constructed using tungsten (HTK W) or molybdenum (HTK MO), resulting in the highest possible purity of the inert atmosphere and final vacuum level. Upon request, a high vacuum upgrade is available. The most commonly used gases include Nitrogen, Argon, Hydrogen, and its mixtures.

The HTK series features heating elements and insulation made of either tungsten (HTK W) or molybdenum (HTK MO). A retort can be utilized to guide the gas flow, particularly for debinding applications or to enhance temperature uniformity. The maximum temperature for the HTK W is 2200 °C, while for the HTK MO, it is 1600 °C.



[Смотреть видео](#)

Видео о приборе: HTK - Камерные печи с металлической теплоизоляцией

ПРИМЕРЫ ПРИМЕНЕНИЯ

carbon free atmosphere, metal injection moulding (MIM), metallization, sintering, thermal debinding, pyrolysis, synthesis, annealing, tempering

ОБЗОР

Furnace Type	Usable Volume	Макс. температура	Количество зон нагрева	Debinding Option
НТК 8 МО/W	8	1600 °C / 2200 °C	1	Torch/ condensate trap
НТК 25 МО/W	25	1600 °C / 2200 °C	1	Torch/ condensate trap
НТК 80 МО	80	1600 °C	4	Torch/ condensate trap
НТК 120 МО	120	1450 °C	4	Torch/ condensate trap

HTK 8



HTK 25



HTK 80



HTK 120



	HTK 8	HTK 25	HTK 80	HTK 120
Usable space in the retort H x W x D [mm]	160 x 180 x 180	240 x 240 x 400	380 x 410 x 500	380 x 400 x 770
Number of plates*	3	3	40	60
Plate dimensions [cm²]*	225	860	930	930
Picture of sample rack				

* The displayed values refer to a typical retort layout. The specific arrangement can be customized to meet the requirements of the customer.

HTK - КАМЕРНЫЕ ПЕЧИ С МЕТАЛЛИЧЕСКОЙ ТЕПЛОИЗОЛЯЦИЕЙ

EXPLANATION OF THE DEBINDING AND SINTERING PROCESS STEPS OF THE HTK-MIM-3 FURNACE

The HTK-MIM-3 furnace program enables debinding and sintering of MIM components in two stages. The program's progress is displayed in a diagram, and important parameters such as pressure, gas flow, and gas type are recorded. The debinding stage utilizes partial pressure and high nitrogen gas flow, while the sintering stage focuses on temperature uniformity, resulting in a consistent density of the MIM parts.




[Смотреть видео](#)

HTK - КАМЕРНЫЕ ПЕЧИ С МЕТАЛЛИЧЕСКОЙ ТЕПЛОИЗОЛЯЦИЕЙ

INSIDE THE FURNACE

HTK 8 – 80 furnaces consist of:


1. Heaters
2. Retort
3. Radiation Shields
4. Thermocouple
5. Gas Inlet
6. Gas Outlet
7. Vacuum Gauge
8. Water-cooled vacuum vessel



Exemplary cross section
of a HTK 8
molybdenum

HTK 120 furnaces consist of:

1. Heaters
2. Radiation Shields
3. Gas inlet
4. Gas Outlet



Heating cassette of the
HTK 120, CAD drawing.
Designed for highest
lifetime and easy
maintenance.

HTK - КАМЕРНЫЕ ПЕЧИ С МЕТАЛЛИЧЕСКОЙ ТЕПЛОИЗОЛЯЦИЕЙ

BINDER HANDLING OPTIONS HTK8 - 80

AFTERBURNER ASSEMBLY:

1. Retort
2. Gas outlet
3. Trace heating
4. Torch
5. Position controlled ball valve



Afterburner

The torch of the afterburner ensures controlled conversion of remaining flammable or toxic volatiles into non-flammable gases.


The condensate trap may be installed for binder handling. During the process the trap is cooled to condense the binder. After the process the trap can be heated to release the binder safely which has been liquified.

HTK - КАМЕРНЫЕ ПЕЧИ С МЕТАЛЛИЧЕСКОЙ ТЕПЛОИЗОЛЯЦИЕЙ

SOME HTK120 OPTIONS

AFTERBURNER ASSEMBLY:

1. Gas outlet
2. Trace heating
3. Torch
4. Position controlled ball valve
5. Fresh oil pump
6. Oil condenser



The stand alone safety purge tank ensures full safety for hydrogen applications. The furnace can only be started, if the tank is completely filled. Therefore the furnace is flood with nitrogen gas in case of major errors, such as power failure etc. The size is adjusted according to the furnace volume.

Heated gas outlet and vacuum line of the HTK 120


Stand alone safety purge tank

HTK - КАМЕРНЫЕ ПЕЧИ С МЕТАЛЛИЧЕСКОЙ ТЕПЛОИЗОЛЯЦИЕЙ


HIGH VACUUM APPLICATIONS

Cross section of HTK 8 with high vacuum upgrade. The turbo pump is at least connected via an DN100 flange.

1. Turbo pump
2. Vacuum valve
3. DN 100 flange



High vacuum upgrade




Schematic of a turbomolecular pump for high vacuum applications.


НТК - КАМЕРНЫЕ ПЕЧИ С МЕТАЛЛИЧЕСКОЙ ТЕПЛОИЗОЛЯЦИЕЙ

CONTROLLER OPTIONS

The furnace is operated via a 12" or 19" touch panel controller. It provides an overview of the furnace and its behaviors and allows the user to preform any possible adjustments to the furnace.



[Смотреть видео](#)



[Смотреть видео](#)

- | User friendly 12" touch panel, provides a detailed overview of the furnace status.
- | Configuration of an automatic programm
- | The smart software is mainly used for simple processes
- | The full automatic function ensures full flexibility
- | The pre-program ensures that the furnace is evacuated prior to heat treatment to ensure safety in case of any occurring errors
- | The system is based on an industrial standard Siemens PLC ensuring full safety.

- | Full visualization of the furnace with 19" touch panel, mainly for fully configured units or for the use of hydrogen (>5%)
- | Configuration of an automatic program
- | The automatic software is used for more complicated and hydrogen processes
- | The CC-IPC1900 version additionally includes an industrial PC with standard windows software
- | The system is based on an industrial standard Siemens F-PLC ensuring full safety even for hydrogen applications
- | The pre-program ensures a fully automated leakage test which takes place in overpressure and vacuum

HTK - КАМЕРНЫЕ ПЕЧИ С МЕТАЛЛИЧЕСКОЙ ТЕПЛОИЗОЛЯЦИЕЙ

ПРИМЕРЫ



HTK 8 MO/16-2G smart
8 L usable volume, 1600
°C, Argon, Forming gas



HTK 25 W/22-1G
automatic 25 L usable
volume, 2200 °C, Argon



HTK 80 MO/16-3G
automatic 80 L usable
volume, 1600 °C, Argon,
Nitrogen, and optional
hydrogen equipment



HTK 120 MO/14-3G
automatic 120 L usable
volume, 1400 °C, Argon,
Nitrogen, Hydrogen,
and partial pressure
option

HTK - КАМЕРНЫЕ ПЕЧИ С МЕТАЛЛИЧЕСКОЙ ТЕПЛОИЗОЛЯЦИЕЙ - ЧАСТО ЗАДАВАЕМЫЕ ВОПРОСЫ

WHAT IS THE ADVANTAGE OF THE CHAMBER FURNACE DESIGN?

Chamber furnaces are quite easy to load and unload, due to the front loading concept. Smaller furnace can be loaded manually, bigger units can be loaded by a manual fork lift. The rectangular design of the water cooled vacuum vessels allows the unit to be designed highly compact. This is why the units do not require much space in the workshop and are perfectly suited for laboratories. All HTK type furnaces are mounted on a single frame and can be easily delivered to customers all over the world. However, for bigger furnace volumes, the vessel is designed cylindrical, as for the HTK 120.

IS A GRAPHITE FURNACE BETTER?

This depends on the process. Some materials, such as stainless steel, 316L, titanium etc. cannot be heat treated in a graphite furnace, especially when the performance of the part is of importance. In such a case metallic furnaces are recommended due to their high purity atmospheres as well as hydrogen and high vacuum abilities.

WHY DOES HYDROGEN HEAT TREATMENT REQUIRE A METALLIC FURNACE?

In a graphite furnace, hydrogen would react with the graphite heating elements and insulation above 1000 °C. The higher the temperature, the faster the graphite parts wear which generates hydrocarbons and causes reactions with the sample. In a metallic furnace the resulting atmosphere is pure.

WHY IS THE INSULATION MADE FROM TUNGSTEN OR MOLYBDENUM?

The lower the variety of materials inside the furnace chamber, the less is the cross-contamination inside the furnace. This leads to a purer atmosphere within the furnace. Furthermore, the working vacuum is better, due to high boiling points and low vapour pressure of the bespoke metals. The Carbolite vacuum furnace design consists of multiple layers of radiation shields to ensure very low energy consumption. Those layers act like a "mirror" reflecting the thermal radiation, hence insulating the furnace. The remaining heat is taken away by cooling water surrounding the vacuum vessel.

WHAT IS THE ADVANTAGE OF (HYDROGEN) PARTIAL PRESSURE?

Carbolite enables adjustable pressure levels between 10 and 1000 mbar. With a variable pressure, the customer can adjust the gas density and therefore the Reynolds number as desired. This ensures a positive gas flow under reduced pressure, evaporating the binder at lower temperatures. This is advantageous for many applications. However, hydrogen partial pressure requires a lot of expertise in order to handle it safely. We use dedicated software and hardware solutions to ensure full safety under these conditions.

МОДЕЛИ

	НТК 8 МО/16-1G	НТК 25 МО/16-1G	НТК 80 МО/16-1G
Изоляционный материал	Молибден	Молибден	Молибден
Габаритные размеры печи В x Ш x Г (мм)	2100 x 1300 x 1100	2200 x 1900 x 1800	2300 x 2100 x 2200
Транспортировочный вес (кг)	1200	1700	2000
Полезное пространство			
Объем (литров)	8	25	80
В x Ш x Г полезный объем без реторты (мм)	200 x 200 x 200	250 x 250 x 400	400 x 400 x 500
В x Ш x Г полезный объем с ретортой (мм)	200 x 180 x 180	230 x 230 x 400	380 x 380 x 500
Температурные значения			
Тмакс, вакуум (°C)	1600	1600	1600
Тмакс, атмосферное давление (°C)	1600	1600	1600
ΔТ, от 500 до 1500 °C (К) в соответствии с DIN 17052	± 5	± 5	± 5
Макс. скорость нагрева (К/мин)	10	10	10
Время охлаждения (ч)	6	6	8
Характеристики питания			
Потребляемая мощность (кВт)	30	80	100
Напряжение (В)	400	400 (3P)	400 (3P)
Ток (А)	75	3x 120	3x 150
Плавкие предохранители, установленные последовательно (А)	3x 100	3x 160	3x 200

	НТК 8 МО/16-1G	НТК 25 МО/16-1G	НТК 80 МО/16-1G
Вакуум (опция)			
Скорость натекания (чистая, холодная, пустая камера) (мбар л/с)	5x10 ⁻³	5x10 ⁻³	5x10 ⁻³
Уровень вакуума, в зависимости от насоса	низкий, средний или высокий вакуум	низкий, средний или высокий вакуум	низкий, средний или высокий вакуум
Требуется охлаждающая вода			
Расход (л/мин)	40	70	100
Макс. температура на входе (°C)	23	23	23
Расход подаваемого газа			
Азот или аргон, другие газы доступны по запросу (л/ч)	200-2000	200-2000	200-2000
Контроллер	по запросу	по запросу	по запросу

	НТК 8 W/22-1G	НТК 25 W/22-1G	НТК 120 MO/16-3G MIM
Изоляционный материал	Вольфрам	Вольфрам	Молибден
Габаритные размеры печи В x Ш x Г (мм)	2100 x 1300 x 1100	2200 x 1900 x 1800	-
Транспортировочный вес (кг)	1300	1900	-
Полезное пространство			
Объем (литров)	8	25	120
В x Ш x Г полезный объем без реторты (мм)	200 x 200 x 200	250 x 250 x 400	-
В x Ш x Г полезный объем с ретортой (мм)	180 x 180 x 200	230 x 230 x 400	-
Температурные значения			
Тмакс, вакуум (°C)	2200	2200	1600
Тмакс, атмосферное давление (°C)	2200	2200	1600
ΔТ, от 500 до 1500 °C (K) в соответствии с DIN 17052	± 5	± 5	± 5
Макс. скорость нагрева (K/мин)	10	10	-
Время охлаждения (ч)	6	6	<4
Характеристики питания			
Потребляемая мощность (кВт)	45	100	100
Напряжение (В)	400	400 (3P)	400 (3P)
Ток (А)	112	3x 150	3x 150
Плавкие предохранители, установленные последовательно (А)	3x 160	3x 200	3x 200
Вакуум (опция)			

	HTK 8 W/22-1G	HTK 25 W/22-1G	HTK 120 MO/16-3G MIM
Скорость натекания (чистая, холодная, пустая камера) (мбар л/с)	-	-	5x10 ⁻³
Уровень вакуума, в зависимости от насоса	низкий, средний или высокий вакуум	низкий, средний или высокий вакуум	низкий, средний или высокий вакуум
Требуется охлаждающая вода			
Расход (л/мин)	40	100	100
Макс. температура на входе (°C)	23	23	23
Расход подаваемого газа			
Азот или аргон, другие газы доступны по запросу (л/ч)	200-2000	200-2000	200-2000
Контроллер	по запросу	по запросу	по запросу

www.carbolite.com/htkmo